

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

IN THE CLAIMS:

The following listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims:

1. (Original) A method for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester comprising:
receiving periodically a global reference time signal at a local CDMA transmitter to periodically set an internal clock of the local CDMA transmitter;
transmitting at least one signal from the local CDMA transmitter;
marking the at least one local CDMA transmitter signal with a unique pattern; including time information in the at least one local CDMA transmitter signal;
receiving the at least one local CDMA transmitter signal containing the time information and the unique pattern at a signal tester that is otherwise obstructed from receiving a global reference time signal;
receiving at the signal tester at least one signal from a CDMA base station;
distinguishing at the signal tester the at least one CDMA base station signal from the at least one local CDMA

Date: November 10, 2004

- 2 -

Atty. Dkt. No.: 2171-017

BEST AVAILABLE COPY

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

transmitter signal, wherein the signal containing the
unique pattern is identified as the at least one local
CDMA transmitter signal;
setting an internal clock within the signal tester based on
the time information included in the at least one local
CDMA transmitter signal;
measuring at the signal tester the at least one CDMA base
station signal; and
evaluating at the signal tester the at least one CDMA base
station signal for signal propagation and coverage.

2. (Currently Amended) The method for CDMA signal testing at
indoor and other locations where a global time synchronization
signal is obstructed from a signal tester of ~~claim~~ claim 1,
wherein there are a plurality of CDMA base stations and the
method further comprising:

receiving at the signal tester at least one signal ~~from a~~ from
the plurality of CDMA base stations;
measuring the at least one CDMA base station signal from each
of the plurality of CDMA base stations; and
evaluating the at least one CDMA base station signal for
signal propagation and coverage form each of the
plurality of CDMA base stations.

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

3. *(Currently Amended)* The method for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of ~~claim~~ claim 1, wherein the transmitting at least one signal from the local CDMA transmitter further comprises transmitting a pilot signal.
4. *(Original)* The method for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 3 wherein the marking the at least one local CDMA transmitter signal with a unique pattern comprises transmitting simultaneously a plurality of closely positioned pilot signals.
5. *(Original)* The method for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 3 wherein the global reference time signals are periodically received from a GPS transmitter and wherein the local CDMA transmitter internal clock is a GPS clock.
6. *(Original)* The method for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 1 wherein the signal tester comprises a psuedonoise scanner.

Date: November 10, 2004

- 4 -

Atty. Dkt. No.: 2171-017

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

7. *(Currently Amended)* The method for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 6 wherein the psuedonoise scanner is a pilot channel scanner and wherein the local CDMA transmitter comprises a pilot transmitter with an internal clock and receiver for receiving periodically global reference time ~~signals~~ signals.
8. *(Original)* The method for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 7 wherein the global reference time signals are received periodically from a GPS transmitter and wherein the internal clock is a GPS clock.
9. *(Original)* The method for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 7 wherein the local CDMA transmitter signal is a pilot signal containing a pilot pattern and time information and further comprising:
- measuring at the signal tester a relative displacement of the pilot pattern of the local CDMA transmitter signal from successive psuedonoise scanner scans of the local CDMA transmitter signal;
 - processing the measured displacement of the pilot pattern;

Date: November 10, 2004

- 5 -

Atty. Dkt. No.: 2171-017

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

and

adjusting a timing generator of the psuedonoise scanner to
compensate for drift in the measured pilot pattern.

10. (Original) The method for CDMA signal testing at indoor and
other locations where a global time synchronization signal is
obstructed from a signal tester of claim 9 wherein adjusting the
timing generator of the signal tester comprises:

modifying a voltage controlled clock oscillator, a digital
to analog converter and an imbedded processor.

11. (Currently Amended) A method for CDMA signal testing at indoor
and other GPS obstructed locations comprising:

receiving periodically at a local CDMA pilot transmitter a
global reference time signal from a GPS for setting an
internal clock for creating time information;

transmitting periodically on a pilot channel a pilot signal
from the local CDMA pilot transmitter;

marking the local CDMA pilot transmitter signal with a unique
pattern;

including time information in the local CDMA pilot transmitter
signal;

transmitting periodically the local CDMA pilot transmitter
signal;

Date: November 10, 2004

- 6 -

Atty. Dkt. No.: 2171-017

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

receiving periodically the local CDMA pilot transmitter signal containing time information and the unique pattern at a signal tester, wherein the signal tester comprises a psuedonoise scanner;

setting an internal clock of the ~~signal~~ signal tester by using the time information contained in the local CDMA pilot transmitter signal;

scanning at the signal tester a pilot signal from a CDMA base station;

distinguishing at the signal tester between the CDMA base station pilot signal and the local CDMA pilot transmitter signal, wherein the signal containing the unique pattern is identified as the local CDMA pilot transmitter signal;

setting an internal clock within the signal tester using the timing information contained in the local CDMA pilot transmitter signal;

compensating for a local CDMA pilot transmission signal pattern drift detected at the signal tester by adjusting a timing generator of the signal tester to modify the signal tester internal clock;

measuring at the signal tester the CDMA base station pilot signal; and

Date: November 10, 2004

- 7 -

Atty. Dkt. No.: 2171-017

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

evaluating at the signal tester the CDMA base station pilot signal for signal propagation and coverage.

12. (Currently Amended) An apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester comprising:

a local CDMA reference transmitter comprising:

a reference internal clock for ~~maintaining~~ maintaining time information;

a receiver for periodically receiving a global reference time signal;

a processor for setting the reference internal clock;

a unique signal pattern for marking a signal;

a transmitter for transmitting a signal, the signal comprising the unique pattern and time information and

a CDMA testing device comprising:

a tester internal clock for maintaining time information;

a receiver for receiving the local CDMA reference transmitter signal and for receiving a signal from a CDMA base station;

a processor for setting the tester internal clock;

a processor for distinguishing between the CDMA reference transmitter signal and the CDMA base station signal; and

Date: November 10, 2004

- 8 -

Atty. Dkt. No.: 2171-017

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

a processor for measuring and evaluating the CDMA base station signal for adequacy of signal propagation and coverage.

13. *(Currently Amended)* The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of ~~claim 12~~ claim 12 wherein the local CDMA reference transmitter comprises a pilot channel transmitter for transmitting pilot signals.

14. *(Original)* The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 13 wherein the unique signal pattern of the local CDMA reference transmitter comprises a plurality of closely positioned pilot signals transmitted simultaneously for creating a recognizable marker.

15. *(Original)* The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 12 wherein the receiver comprises a GPS receiver for periodically receiving a GPS synchronized time signal and wherein the reference internal clock comprises a GPS clock for maintaining the GPS synchronized time.

Date: November 10, 2004

- 9 -

Atty. Dkt. No.: 2171-017

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

16. *(Currently Amended)* The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 13 wherein the testing device ~~comprises~~ comprises a psuedonoise scanner for scanning for psuedonoise.
17. *(Original)* The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 16 wherein the local CDMA reference transmitter comprises a transmitter for transmitting a pilot channel signal and wherein the psuedonoise scanner comprises a scanner for scanning a pilot channel.
18. *(Currently Amended)* The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 15 wherein the ~~universal~~ universal reference time signal further comprises a GPS time signal for synchronizing time and wherein the reference internal clock comprises a GPS clock for maintaining GPS synchronized time.
19. *(Currently Amended)* The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

signal is obstructed from a signal tester of claim 12 further comprising:

a means for detecting time drift comprising:

logic for measuring relative displacement of the local

CDMA reference transmitter unique signal pattern from

~~successive~~ successive psuedonoise scanner scans of the

local CDMA reference transmitter pilot channel signal;

and

logic for processing the relative displacement of

~~successive measurements~~ measurements of the local CDMA

reference transmitter unique signal pattern and

a means for adjusting the tester internal clock further comprising:

a timing generator for adjusting the signal tester internal clock; and

a timing generator adjustor for adjusting the timing generator to compensate for drift in the local CDMA reference transmitter pilot pattern.

20. (Currently Amended) The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 19 wherein the timing generator adjustor comprises a delay lock loop for

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

adjusting a timing generator to ~~compensate~~ compensate for a detected timing drift.

21. (Original) The apparatus for CDMA signal testing at indoor and other locations where a global time synchronization signal is obstructed from a signal tester of claim 20 wherein the delay lock loop further comprising:

logic for modifying a voltage controlled clock oscillator;
logic for modifying a digital to analog converter; and
logic for modifying an imbedded processor.

22. (Currently Amended) An apparatus for CDMA signal testing at indoor and other GPS obstructed locations comprising:

a local CDMA reference transmitter comprising:

a reference internal GPS clock for ~~maintianing~~
maintaining time information;

a receiver for periodically receiving reference time signals from GPS;

a processor for setting the reference internal GPS clock;

a pilot channel transmitter for transmitting a pilot channel signal;

a unique signal pattern for marking the local CDMA pilot channel signal; and

a CDMA testing device comprising:

AMENDMENT UNDER 37 C.F.R. § 1.111
Appln. No. 09/781,002

PATENT APPLICATION

a psuedonoise scanner for receiving pilot channel signals
from the local CDMA reference transmitter and for
receiving a pilot channel signal from a CDMA base
station;
a tester internal clock for maintaining time information;
and
a processor comprising;
logic for distinguishing between a pilot channel signal
from the local CDMA reference transmitter and a
pilot channel signal from the CDMA base station;
logic for setting the tester internal clock,
logic for adjusting a timing generator of the
psuedonoise scanner so as to compensate for drift in
the measured pilot pattern, and
logic for measuring and evaluating the received signals
for adequacy of signal propagation and coverage from
the at least one CMA base station.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.